



A Textron Company

MODEL: INDUSTRIAL 800
TYPE: GASOLINE POWERED TRUCK
MODEL YEAR: 2008

Part No.: 605813, 606685 California



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 13 hp (9.7 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki

- **Valve Train:** Overhead valve
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Balancer:** Internal counter rotating balance shaft
- **Fuel System:** Fixed float bowl with remote pulse fuel pump
- **Ignition:** Solid-state, electronic advance, RPM limiter
- **Air Cleaner:** Replaceable dry cartridge

Electrical: Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)

Drive Train: Automatic, continuously variable transmission (CVT)

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system

Transaxle: Differential with helical gears, ground speed governor, forward/reverse

Cargo Bed: Roto-molded cross-linked polyethelene. Lifts for access to powertrain. Removable hinged multi-position tailgate requires no latch mechanism

PRODUCT OVERVIEW

Dimensions

Overall Length	103.0 in (260 cm)
Overall Width	46.5 in (118 cm)
Overall Height (No Canopy)	48.6 in (123 cm) (Top of steering wheel)
Overall Height (With Canopy)	78.0 in (183 cm)
Wheel Base	65.5 in (166 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.0 in (97 cm)
Gnd Clearance @ Differential	6.0 in (15 cm)
Cargo Box Width (inside)	44.5 in (113 cm)
Cargo Box Length (inside)	30.5 in (77 cm)
Cargo Box Depth (inside)	7.5 in (19 cm)
Cargo Box Capacity	5.9 cu ft (0.17 m3)
Cargo Box Material	Roto-molded polyethylene

Performance

Seating Capacity	2 Persons
Dry Weight	750 lb (340 kg)
Curb Weight	780 lb (355 kg)
Bed Load Capacity	500 lb (225 kg)
Vehicle load capacity	800 lb (360 kg)
Outside Clearance Circle	18.9 ft (5.8 m)
Intersecting Aisle Clearance	N/A
Speed (Level Ground)	Fwd - 14.0 mph ± 0.5 mph (22.5 kph ± 0.8 kph) Rev - 10.1 mph ± 0.5 mph (16.3 kph ± 0.8 kph)
Towing Capacity	500 lb (225 kg)

Steering & Suspension

Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single point engagement
Front Tires	5.70 x 8 - 8 (Load Range C)
Rear Tires	5.70 x 8 - 8 (Load Range C)

Body & Chassis

Frame	Welded steel with DuraShield™ powder coat
Front Body & Finish	Injection molded Geloy XTW
Rear Body & Finish	Steel. Base coat/clear coat
Standard Color	Yellow

Vehicle Power

Power Source	4 Cycle 24.5 cu in (401 cc)
Valve Train	Single Cylinder OHV
Horsepower (kW)	13 hp (9.7 kW) Exceeds SAE J1940 Std.
Electrical System	Starter/Generator. Solid State Regulator
Batteries (Qty, Type)	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal
Air Cleaner	Industrial Rated Dry Filter
Lubrication	Pressurized Oil System
Oil Filter	Spin-On
Cooling System	Air Cooled
Fuel Capacity	5.8 Gallon (22.0 L) tank
Drive Train	Continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward - Reverse
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)

Some items shown may be optional equipment



A Textron Company

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld	Item	Std	Opt	Fld
TIRES & WHEELS:				HAULING & TOWING:			
Front & Rear:				1 7/8 in (48 mm) Ball (Rcvr Reqd)			
5.70 x 8 - 8 (Load Range C)	●			1 7/8 in (48 mm) Ball, Drop (Rcvr Reqd)		●	
18.50 x 8.50 - 8 (Load Range C)		●		2 in (5 cm) Receiver (Rear)		●	
Wheel Covers:				Angle Hitch (Rcvr Reqd)			
Spoke, Black & Gold		●		Angle Hitch, Drop (Rcvr Reqd)		●	
Spoke, Black & Silver		●		Clevis Hitch (Rcvr Reqd)		●	
COLORS:				Clevis Hitch, Drop (Rcvr Reqd)			
Body Color (Yellow)	●			Gas Spring Assisted Load Bed		●	
Body Color (Ivory)		●		Power Dump (Electric)		●	
Body Color (Forest Green)		●		Trailer, Dump (Poly Bed)			●
Body Color (Bright White)		●		Trailer, Dump (Steel Bed)			●
Body Color (Black)		●		WEATHER PROTECTION:			
Body Color (Flame Red)		●		Brush Guard Cage for Windshield & Top			
Seating:				Sun Canopy (Top) Champagne			
Seat Color (Black)	●			Sun Canopy (Top) Tan			●
Seat Color (Oyster)		●		Sun Canopy (Top) Tan (Brush Guard Cage Required)			●
Seat Color (White)		●		Weather Enclosure, Tan (3 Side, Top & Windshield Req'd)			●
Seat Color (Tan)		●		Weather Enclosure, White (3 Side, Top & Windshield Req'd)			●
OTHER PERFORMANCE:				Windshield (Brush Guard Cage Required)			
Ash Tray		●		Windshield Flat			●
Front Bumper & Guard (Black)		●		Windshield Flat Lexan®			●
Front Hydraulic Disc Brakes		●		Windshield Fold Down			●
Glove Box Door (Locking) Driver Side		●		Windshield Fold Down Lexan®			●
Glove Box Door (Locking) Passenger Side		●		VEHICLE CAB			
High Altitude Jetting 3 - 6K ft (900 - 1800 m)		●		Steel Cab (Tan):			
High Altitude Jetting 6K + ft (1800 + m)		●		Steel Cab (White):			
Rear View Mirror (Sun Canopy Required)			●	Steel Cab (Non Standard Color):			
Shield, Clutch Belt		●		Beacon, Amber (Cab Required)			
Spark Arrestor		●		Defroster/Fan (Cab Required)			
ELECTRICAL:				Dome Light (Cab Required)			
Brake Lights		●		Doors (Steel) Tan (Cab Required)			
Headlights		●		Doors (Steel) White (Cab Required)			
Headlights & Taillights		●		Doors (Steel) Non Standard Color (Cab Required)			
Strobe Light		●		Doors (Vinyl) Tan (Cab Required)			
Turn Signals with 4-Way Flashers		●		Heater (Cab Required)			
Work Lights		●		Rear View Mirror (Cab Required)			
Work Lights with Strobe Light		●		Strobe Light (Cab Required)			
Miscellaneous:				Windshield Wiper (Cab Required)			
12 Volt Outlet		●		Work Light (Cab Required)			
CE Kit		●					
DC Converter		●					
Heavy Duty Battery		●					
Horn	●						
Hour Meter		●					
Unique Individual Key Switch		●					