

Power		
Power Source	Diesel	Gas
Engine	Kubota D722, 719 cc, 3-cylinder	Kawasaki 4 cycle, OHV, 675 cc, twin-cylinder industrial grade
Engine - Cooling	Liquid	Air
Engine - Lubrication & Oil Filter Type	Full-pressure, spin-on	Full-pressure, spin-on
Max Torque	33 ft-lb (44.7 Nm)	39.8 ft-lb (54 Nm)
Horsepower	20 hp (14.9 kw)	23 hp (17.2 kw)
Ignition	Compression	Transistorized magneto
4WD Engagement	Automatic – IntelliTrak	Automatic – IntelliTrak
Differential - Front	Automatic – IntelliTrak	Automatic – IntelliTrak
Differential - Rear	Auto locking – IntelliTrak	Auto locking – IntelliTrak
Torque Converter	CVT	CVT
Electrical System	12-volt, 500 CCA	12-volt, 500 CCA

Agility		
Power Source	Diesel	Gas
Steering	Rack & pinion	Rack & pinion
Tilt Steering Wheel	Standard	Standard
Seating	Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option	Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option
Suspension - Front	Independent double A-arms w/coil-over shocks	Independent double A-arms w/coil-over shocks
suspension - Rear	Swing arm w/coil-over shocks	Swing arm w/coil-over shocks
Brakes	4-wheel, hydraulic disc	4-wheel, hydraulic disc
Park Brake	Automotive style	Automotive style

Strength / Design		
Power Source	Diesel	Gas
Frame Chasis	Tubular aluminum	Tubular aluminum
Body - Front	GE Geloy High-impact, scratch-resistant, injection molded color	GE Geloy High-impact, scratch-resistant, injection molded color
Body - Rear	All aluminum cargo bed	All aluminum cargo bed
Tires - Front	All-terrain, 25 x 10.5-12, 4-ply (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply (mud tires optional)
Tires - Rear	All-terrain, 25 x 10.5-12, 4-ply (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply (mud tires optional)
Instrumentation	Electronic fuel gauge/hour meter, low	Electronic fuel gauge/hour meter,

	oil warning light, coolant high temp warning light (speedometer optional)	low oil warning light (speedometer optional)	
Flat Bed Size	48.8in x 49.8in x 10.9in (124 x 126.5 x 27.7 cm)	48.8in x 49.8in x 10.9in (124 x 126.5 x 27.7 cm)	
Bed Height	33in (83.8 cm)	33in (83.8 cm)	
Bed Capacity	800 lb (362 kg); 1,050 lb (476.3 kg) available	800 lb (362 kg); 1,050 lb (476.3 kg) available	
Total Vehicle Capacity	1,200 lb (544.3 kg); 1,450 lb (657.7 kg) available	1,200 lb (544.3 kg); 1,450 lb (657.7 kg) available	
Overall Length	124.6in (316.5 cm)	124.6in (316.5 cm)	
Overall Width	60in (152.4 cm)	60in (152.4 cm)	
Overall Height	78.6in (199.6 cm)	78.6in (199.6 cm)	
Wheelbase	88.7in (225.3 cm)	88.7in (225.3 cm)	
Ground Clearance	7.4in (18.8 cm)	7.4in (18.8 cm)	
Fuel Tank Capacity	6.5 gal (24.6 L)	6.5 gal (24.6 L)	
Tread (Front/Rear)	48.8in (124 cm) front and rear	48.8in (124 cm) front and rear	
Dry Weight Less Batteries	1,559 lb (707.2 kg)	1,430 lb (648.6 kg)	
Maximum Speed	25 mph (40.2 kph)	25 mph (40.2 kph)	
Turning Radius	13.0 ft (3.8 m)	13.0 ft (3.8 m)	
Vehicle Warranty	2-year/2,000-hour, limited	2-year/2,000-hour, limited	