

Power	
Engine	11 hp, 4-cycle, OHV, 351 cc
Drive Unit	Unitized transaxle, fully synchronized forward and reverse with neutral (11.8 to 1 forward, 17.1 to 1 reverse); reduced speed reverse
Batteries	12-volt, 500 cca at 0°F (-18°C), 105 minute reserve

Agility	
Steering	Self-adjusting rack & pinion
Suspension - Front	Independent leaf spring with dual hydraulic shocks
suspension - Rear	Multi-leaf spring with dual hydraulic shocks
Brakes	Four-wheel mechanical drum
Stabilizer Bar	Anti-sway

Strength / Design	
Frame Chasis	Aluminum I-Beam
Body	ArmorFlex®
Body Finish	Matching paint over molded-in color
Tires - Front	18 x 8.50-8, 6-ply rated, Premium tread
Tires - Rear	18 x 8.50-8, 6-ply rated, Premium tread
Seating Capacity	2 passengers
Total Vehicle Capacity	Up to 1200 lb. (544.3 kg)
Overall Length	111.0" (281.9 cm)
Overall Width	50.0" (127.0 cm)
Overall Height	48.0" (121.9 cm)
Wheelbase	77.5" (196.9 cm)
Ground Clearance	4.5" (11.4 cm)
Tread (Front/Rear)	34.5" (87.6 cm)
Maximum Speed	14.0 mph (22.5 kph)
Curb Clearance Circle	296.0" (7.5 m)
Turning Radius	120.0" (304.8 cm)
Vehicle Warranty	2 year