

Specifications

Carryall 252 Gasoline

POWER SUPPLY	Engine	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
	Horsepower	11.5*
	Governor	Automatic ground speed sensing, internally geared-in unitized transaxle
	Governed RPM	2900+/- 30
	Ignition	Electronic w/electronic RPM limiter
	Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
	Electrical System	12-volt, 500 cca 105 min. reserve
STEERING/ SUSPENSION	Steering	Self-adjusting rack & pinion
	Front Suspension	Independent leaf spring with dual hydraulic shocks
	Rear Suspension	Leaf springs with dual hydraulic shocks
	Brakes	Four-wheel mechanical drum
	Park Brake	Foot-operated, multi-lock
	Stabilizer Bar	Yes
FRAME/CHASSIS	Frame/Chassis	Aluminum I-Beam
	Front Body	ArmorFlex®
	Rear Body	All aluminum
	Body Finish	Matching paint over molded-in color
	Light Package	Headlights only package
	Trailer Hitch	Standard
	Front Tires	22 x 11.00-10, 6-ply rated, Heavy-duty All-Terrain tread
	Rear Tires	22 x 11.00-10, 6-ply rated, Heavy-duty All-Terrain tread
	Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
DIMENSIONS	Cargo Box Size	48.8" x 49.8" x 10.9" (123.8 cm x 126.4 cm x 27.6 cm)
	Flat Bed Size	46.9" x 48.3" (119.1 cm x 122.7 cm)
	Bed Height	27.5" (69.9 cm)
	Bed Capacity	500 lb. (226.8 kg)
	Total Vehicle Capacity	900 lb. (408.2 kg)
	Overall Length	120.4" (305.8 cm)
	Overall Width	51.3" (130.2 cm)
	Overall Height	51.1" (129.8 cm)
	Wheelbase	78.5" (199.4 cm)
	Ground Clearance Under Differential	6.4" (16.3 cm)
	Fuel Tank Capacity	7.0 gallons (26.5 Liters)
	Tread	36.5"/41.3" (92.7 cm/104.8 cm)
	Dry Weight Less Batteries	910 lb. (412.8 kg)
	Speed Range	15-17 mph (24.1-27.4 kph)
	Outside Clearance Circle	21.7 ft. (6.6 m) dia.
	Turning Radius	10.8 ft. (3.3 m)
	Intersecting Aisle Radius	77.0" (195.6 cm)
Vehicle Warranty	2-year limited	

*Exceeds SAE J1940 Performance Standards