

Specifications

		<i>Carryall 295 SE Gasoline</i>	<i>Carryall 295 SE Diesel</i>
POWER SUPPLY	Engine	Honda GX620, 614 cc, 2-cylinder	Kubota D722, 719 cc, 3-cylinder
	Engine – Cooling	Air	Liquid
	Engine – Lubrication & Oil Filter Type	Full-pressure spin-on	Full-pressure spin-on
	Max Torque	32.5 ft-lb (44.1 Nm)	33 ft-lb (44.7 Nm)
	Horsepower	20 (14.9 kw)	20 (14.9 kw)
	Ignition	Transistorized magneto	Compression
	4WD Engagement	Automatic – IntelliTrak	Automatic – IntelliTrak
	Differential – Front	Automatic – IntelliTrak	Automatic – IntelliTrak
	Differential – Rear	Auto locking – IntelliTrak	Auto locking – IntelliTrak
	Electrical System	12-volt, 500 CCA	12-volt, 500 CCA
	Torque Converter	CVT	CVT
STEERING/ SUSPENSION	Steering Type	Rack & pinion	Rack & pinion
	Tilt Steering Wheel	Standard	Standard
	Adjustable Driver's Seat	Only available with bucket seat option	Only available with bucket seat option
	Suspension – Front	Independent double A-arms w/coil-over shocks	Independent double A-arms w/coil-over shocks
	Suspension – Rear	Swing arm w/coil-over shocks	Swing arm w/coil-over shocks
	Brakes	4-wheel, hydraulic disc	4-wheel, hydraulic disc
	Park Brake	Automotive style	Automotive style
FRAME/CHASSIS	Frame/Chassis	Tubular aluminum	Tubular aluminum
	Body – Front	GE Geloy High-impact, scratch-resistant, injection molded color	GE Geloy High-impact, scratch-resistant, injection molded color
	Body – Rear	All aluminum cargo bed	All aluminum cargo bed
	Tires – Front	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Tires – Rear	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Instrumentation	Electronic fuel gauge/hour meter, low oil warning light (speedometer optional)	Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light (speedometer optional)
DIMENSIONS	Bed Length x Width x Height	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
	Overall Bed Height	33 in (83.8 cm)	33 in (83.8 cm)
	Bed Load Capacity	800 lb (362.9 kg)*	800 lb (362.9 kg)*
	Total Vehicle Capacity	1,200 lb (544.3 kg)**	1,200 lb (544.3 kg)**
	Fuel Tank Capacity	6.5 gal (24.6 L)	6.5 gal (24.6 L)
	Overall Length x Width x Height	157.6 x 60 x 78.6 in (400.3 x 152.4 x 199.6 cm)	157.6 x 60 x 78.6 in (400.3 x 152.4 x 199.6 cm)
	Wheelbase	88.7 in (225.3 cm)	88.7 in (225.3 cm)
	Ground Clearance – Differential	7.4 in (18.8 cm)	7.4 in (18.8 cm)
	Tread Centers (Front/Rear)	48.8 in (124 cm) front and rear	48.8 in (124 cm) front and rear
	Dry Weight (Less Batteries)	1,339 lb (599 kg)	1,475 lb (669.1 kg)
	Maximum Speed	25 mph (40.2 kph)	25 mph (40.2 kph)
	Turning Radius	12.1 ft (3.7 m)	12.1 ft (3.7 m)
Vehicle Warranty	2-year/2,000-hour, limited	2-year/2,000-hour, limited	

*1,050 lb (476.3 kg) available
 **1,450 lb (657.7 kg) available