


Power	
Power Source	Gas
Engine	Kawasaki 4-cycle, OHV, 400 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	13 hp @ 3,600 rpm , exceeds SAE J1940 Performance Standards.
Governed RPM	3,800 +/- 30
Ignition	Electronic w/electronic rpm limiter
Drive Unit	Unitized transaxle, helical gears: 15.0:1 forward, 20.6:1 reverse
Electrical System	12-volt, 500 cca 105 min. reserve

Agility	
Power Source	Gas
Steering	Self-adjusting rack & pinion
Suspension - Front	Independent A-arms w/ coil-over shocks
Brakes	Self adjusting dual-circuit, 4-wheel hydraulic drum
Park Brake	Hand-operated, multi-lock

Strength / Design	
Power Source	Gas
Frame Chasis	Aluminum I-Beam
Body - Front	ABS/DR acrylic laminate
Tires	23 x 10.5-12, 4-ply rated, All-terrain tread
Cargo Box Size	48.8in x 49.8in x 9.3in / 304.8 (13 ft3) 123.8 cm x 126.4 cm x 23.5 cm
Flat Bed Size	46.9in x 48.3in (119.1 cm x 122.7 cm)
Bed Height	31.1in (79 cm)
Bed Capacity	800 lb. (362.9 kg)
Total Vehicle Capacity	1,200 lb. (544.3 kg)
Overall Length	120in (304.8 cm)
Overall Width	54in (137.2 cm)
Overall Height	51.0in (129.5 cm)
Wheelbase	80in (203.2 cm)
Ground Clearance	6.6in (16.8 cm) 11.4in/29.0 cm Under Foot Platform
Fuel Tank Capacity	7 gallons (26.6L)
Tread (Front/Rear)	43in/43.5in (109.2 cm/ 110.5 cm)
Dry Weight Less Batteries	1,022 lb. (463.6 kg)
Speed Range	17-19 mph (27.4-30.6 kph)
Outside Radius Circle	23.3 ft. (7.1 m) dia.
Turning Radius	90in (228.6cm)

Intersecting Aisle Radius	11.8 ft. (3.6 m)	
Vehicle Warranty	2-year, limited	