

<b>Power</b>	
Power Source	Gas
Engine	400 cc, Kawasaki, gasoline key-start engine
Horsepower	13 @ 3,600 rpm , exceeds SAE J1940 Performance Standards.
Governor	Automatic ground speed sensing,internally geared-in unitized transaxle
Governed RPM	3800±30
Ignition	Electronic w/electronic limiter
Drive Unit	Unitized transaxle, helical gears: 15.0: 1 forward, 20.6: 1 reverse
Electrical System	12-volt, 500 CCA 105 min. reserve
Key or Pedal Start	Key

<b>Agility</b>	
Power Source	Gas
Steering	Self-adjusting rack & pinion
Suspension - Front	Independent A-arms with coil over shocks
suspension - Rear	Leaf springs with dual hydraulic shocks
Brakes	Self-adjusting, dual circuit, 4-wheel hydraulic drum
Park Brake	Hand-operated, multi-lock
Stabilizer Bar	No

<b>Strength / Design</b>	
Power Source	Gas
Frame Chasis	Rust-proof non-corrosive,aircraft-grade 6061 aluminum frame
Body - Front	ABS/DR-Acrylic laminate
Body - Rear	All aluminum
Body Finish	Molded-in color
Light Package	Dual halogen headlights
Trailer Hitch	Standard
Tires - Front	23 x 10.50-12,4-ply rated, All-terrain tread; available mud tires
Tires - Rear	23 x 10.50-12,4-ply rated, All-terrain tread; available mud tires
Instrumentation	Electronic fuel gauge/hour meter,low-oil warning light
Cargo Box Size	48.8 x 49.8 x 9.3 in (123.8 cm x 126.4 cm x 23.5 cm)

Flat Bed Size	46.9 x 48.3 in (119.1 cm x 122.7 cm)
Bed Height	31.1 in (79.0 cm)
Bed Capacity	800 lb. (362.9 kg)
Total Vehicle Capacity	1200 lb. (544.3 kg)
Overall Length	120 in (304.8 cm)
Overall Width	54.0 in (137.2 cm)
Overall Height	51.0 in (129.5 cm)
Wheelbase	80.0 in (203.2 cm)
Ground Clearance	6.6 in (16.8 cm)
Fuel Tank Capacity	7.0 gal (26.5 L)
Tread (Front/Rear)	43 in/43.5 in (109.2 cm/110.5 cm)
Dry Weight Less Batteries	1045 lb. (474.0 kg)
Maximum Speed	19 mph (30.6 kph)
Turning Radius	11.8 ft (3.6 m)
Vehicle Warranty	2-year/2,000 hour, limited