

Power	
Power Source	Diesel
Engine	Kubota® 719 cc, 3-cylinder, industrial grade
Engine - Cooling	Liquid
Engine - Lubrication & Oil Filter Type	Full-pressure; spin-on
Max Torque	33 ft-lb (44.7Nm)
Horsepower	20 hp (14.9 kw)
Ignition	Compression
4WD Engagement	Automatic - IntelliTrak All-Wheel-Drive
Differential - Front	Automatic - IntelliTrak All-Wheel-Drive
Differential - Rear	Auto locking - IntelliTrak All-Wheel-Drive
High-Low Range Engagement	Automatic
Torque Converter	CVT
Electrical System	12-volt, 500 CCA

Agility	
Power Source	Diesel
Steering	Rack & pinion
Tilt Steering Wheel	Standard
Seating	Standard
Suspension - Front	Independent double A-arms w/ coil-over shocks
suspension - Rear	Swing arm w/ coil-over shocks
Brakes	4-wheel, hydraulic disc
Park Brake	Foot-operated

Strength / Design	
Power Source	Diesel
Frame Chasis	Rust-proof non-corrosive, aircraft-grade 6061 aluminum frame
Body - Front	High-impact, scratch-resistant, GE Gelyo injection molded color
Body - Rear	Rugged, scratch-resistant injection molded plastic
Tires - Front	Mud, 25 x 11-12, 4-ply, (optional all-terrain tires available)
Tires - Rear	Mud, 25 x 11-12, 4-ply, (optional all-terrain tires available)
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light, coolant high-temp warning light (speedometer optional)
Cargo Box Size	48 x 49.8 x 10.9 in (121.9 x

	126.5 x 27.7 cm)	
Bed Height	33 in (83.8 cm)	
Bed Capacity	800 lb (362.9 kg)	
Front Load Capacity	500 lb (227.3 kg)	
Total Vehicle Capacity	1,700 lb (771.1 kg)	
Overall Length	148.6 in (377.4 cm)	
Overall Width	60 in (152.4 cm)	
Overall Height	78.6 in (199.6 cm)	
Wheelbase	81.5 in (207 cm)	
Ground Clearance	7.4 in (18.8 cm)	
Ground Clearance Under Foot Platform	12.1 in (30.7 cm)	
Fuel Tank Capacity	6.5 gal (24.6 L)	
Tread (Front/Rear)	48.8 in (124 cm)/48.8 in (124 cm)	
Dry Weight Less Batteries	1,709 lb (775.2 kg)	
Maximum Speed	25 mph (40.2 kph)	
Turning Radius	13.8 ft (4.2 m)	
Vehicle Warranty	2-year/2,000-hour, limited	