

Power	
Engine	Kawasaki 4-cycle, OHV, 400 cc, single cylinder, air-cooled, pressure lubricated, spin-on oil filter
Horsepower	13.0 rated
Governor	Automatic ground speed sensing, internally geared in unitized transaxle
Governed RPM	2800 ± 30
Ignition	Electronic with electronic RPM limiter
Drive Unit	Unitized transaxle, fully synchronized forward/reverse with neutral: 14.9:1 forward, 20.5:1 reverse; reduced speed reverse
Electrical System	12-volt
Batteries	500 cca at 0°F (-18°C), 105 min. reserve
Charger	Key

Agility	
Steering	Self-adjusting rack & pinion
Suspension - Front	Independent a-arm with coil-over shocks
suspension - Rear	Multi-leaf springs w/dual hydraulic shocks
Brakes	Four-wheel hydraulic
Park Brake	Hand-operated, mechanical rear

Strength / Design	
Frame Chasis	Aluminum I-Beam
Body - Front	ABS/DR acrylic cap
Body - Rear	All aluminum
Body Finish	Acrylic cap
Light Package	Standard
Trailer Hitch	Standard (front receiver)
Tires - Front	205/65-10, 6-ply
Tires - Rear	205/65-10, 6-ply
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
Bed Capacity	650 lb. (294.8 kg)
Overall Length	144.4" (366.8 cm)
Overall Width	50.0" (127.0 cm)
Overall Height	72.0" (182.9 cm)
Wheelbase	101.0" (256.5 cm)
Ground Clearance	6.6" (16.8 cm)
Fuel Tank Capacity	6.5 gallons (24.6 liters)
Tread (Front/Rear)	43.0" front (109.2 cm), 44.5" rear (113.0 cm)
Dry Weight Less Batteries	1474 lb. (668.6 kg)
Maximum Speed	12.0 mph (19.3 kph)
Outside Radius Circle	380.0" (965.2 cm) dia.

Turning Radius	186.0" (472.4 cm)	
Intersecting Aisle Radius	120.0" (304.8 cm)	
Vehicle Warranty	2 year limited	