

Power	
Power Source	Gas
Engine	Kawasaki 4-cycle, OHV, 351 cc single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	11.5 hp @ 3,600 rpm , exceeds SAE J1940 Performance Standards.
Governor	Automatic ground speed sensing, Internally geared-in unitized transaxle
Governed RPM	3,050 +/- 30
Ignition	Electronic w/electronic rpm limiter
Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
Electrical System	12-volt, 500 CCA 105 min. reserve
Key or Pedal Start	Key

Agility	
Power Source	Gas
Steering	Self-adjusting rack & pinion
Suspension - Front	Independent leaf spring with dual hydraulic shocks
Brakes	4-wheel, mechanical drum
Park Brake	Foot-operated, multi-lock
Stabilizer Bar	Yes

Strength / Design	
Power Source	Gas
Frame Chasis	Aluminum I-Beam
Body - Front	ArmorFlex®
Body - Rear	All aluminum
Body Finish	Matching paint over molded-in color
Light Package	Optional
Trailer Hitch	Standard
Tires - Front	18 x 6.50-8, 6-ply rated, premium tread
Tires - Rear	18 x 8.50-8, 6-ply rated, premium tread
Instrumentation	Electronic fuel gauge/hour meter low-oil warning light

Cargo Box Size	70.5in x 45.1in x 9.3in (17.1 ft3) 179.1 cm x 114.6 cm x 23.5 cm
Flat Bed Size	67.6in x 44.2in (171.8 cm x 112.2 cm)
Bed Height	27in (68.6 cm)
Bed Capacity	1,000 lb. (499.4 kg)
Total Vehicle Capacity	1,500 lb. (681 kg)
Overall Length	134in (340.4 cm)
Overall Width	49.3in (125.2 cm)
Overall Height	48.0in (121.9 cm)
Wheelbase	98.5in (250.2 cm)
Ground Clearance	4.5in (11.4 cm)
Fuel Tank Capacity	6 gallons (22.7L)
Tread (Front/Rear)	34.5in/38.5in (87.6 cm/97.8 cm)
Dry Weight Less Batteries	868 lb. (394.1 kg)
Speed Range	14-16 mph (22.5-25.7 kph)
Outside Radius Circle	24.7 ft. (7.5 m) dia.
Turning Radius	12 ft. (3.7 m)
Intersecting Aisle Radius	90in (228.6 cm)
Vehicle Warranty	2-year limited